


OUTDOOR STRETCH DOUBLE




Double-coated, waterproof stretch fabric, ideal for outdoor use. Not suitable for permanent outdoor use.

SPECIFICATIONS

Item	Width	Length	Weight	Composition
2965	145 cm	± 100 m	400 g/m ²	60% PES + 40% PU

FR standard

NF P 92-507 / M2

Care instructions	Breaking extension	Breaking strength
	ISO 13934: 1999 Warp: 90 % Weft: 120 %	ISO 13934: 1999 Warp: 400 N/5cm Weft: 300 N/5cm
Tear strength	Washing shrinkage	Waterproofness
ISO 4674A1: 1977 Warp: 50 N Weft: 45 N	ISO 5077: 1984 Warp: 0 [±4] % Weft: 0 [±2] %	ISO 811: 1981 Before washing: 2000 mm After washing: 2000 mm

EXTRA INFO

A. WASHING

Washing (40°C or 95°C) must be done with neutral detergents; softening agents are not allowed. Undyed fabrics may be washed following the ISO 6330 norm, Part 9A and dyed fabrics following the ISO 6330 norm Part 3A.

B. DISINFECTIONS

In general, the PVC-coated products resist well to most of the currently used surface disinfectants. Nevertheless, we advise to test the particular surface disinfectant in advance or to contact us in case.

C. DRYING


Adequate drying is a crucial factor in the care and maintenance of coated articles. Drying may be effected by hanging out, spinning or tumbling at temperatures up to 60°C. Do not press or mangle!

D. STORING

Store in a dry area, at room temperature. Avoid excessive pressure and contact with non-colourfast materials. Try not to expose the PVC-Coating to excessive sunlight (UVradiation).

OUTDOOR STRETCH DOUBLE

AVAILABLE COLOURS



0613